


PIN	DESCRIPTION
1	LEDK
2	LEDA
3	GND
4	VDD
5	NC
6	NC
7	/CS
8	/RESET
9	RS
10	/WR
11	RD
12	DB7
13	DB6
14	DB5
15	DB4
16	DB3
17	DB2
18	DB1
19	DB0
20	GND



LED CIRCUIT DIAGRAM

- NOTES:
1. DISPLAY MODE:1.8" TFT LCD, Transmissive
 2. DRIVER IC:ILI9361V
 3. VIEWING DIRECTION:12 O'CLOCK
 4. BACKLIGHT:2 CHIP-WHITE LED,IF=40mA, VF=3.2V
 5. OPERATING TEMPERATURE:-20°C TO 70°C
 6. STORAGE TEMPERATURE:-30°C TO 80°C
 7. GENERAL TOLERANCE:±0.20

TOLERANCE	SCALE	N.T.S
.X	±	mm
.XX	±	mm
	± 1°	

HONSEAN 深圳市弘盛智能科技有限公司
SHENZHEN HONSEAN SMART DISPLAY TECHNOLOGY CO.,LTD

DRG DATE: _____ MODEL: G018C120T02N
 DRG BY: Welly TITLE: _____
 APPROVED: Jan P/N: _____